



Model	XMS-9060W-G5i/i3200u/XP600/G5/G6						
	Honson/WUHAN/DPCS/UMCmainboard						
Appearance	Black grey + medium grey						
Print Head	Ricoh GEN5i/i3200u/G5/G6/XP600(1-4)						
Rail	Double rail						
Color	CMYK+Lc+Lm+White+Varnish						
Printing Speed (sqm/h)	Print head	GEN5	GEN6	GEN5i	i3200u	XP600	
	720x600dpi(4PASS)	26m <sup>2</sup> /h	32m <sup>2</sup> /h	4m <sup>2</sup> /h	10m <sup>2</sup> /h	4m <sup>2</sup> /h	
	720x 900dpi(6PASS)	20m <sup>2</sup> /h	24m <sup>2</sup> /h	3m <sup>2</sup> /h	8m <sup>2</sup> /h	3m <sup>2</sup> /h	
	720x1200dpi(8PASS)	15m <sup>2</sup> /h	18m <sup>2</sup> /h	2m <sup>2</sup> /h	6m <sup>2</sup> /h	2m <sup>2</sup> /h	
Print size(mm)	940x640						
PrintThickness(mm)	Platform lifting 380mm Cylinder print diameter 20mm~200mm(Ultra-high customizable)						
Curing System	LED UVLights						
Image Format	TIFF/JPG/EPS/PDF/BMP						
Rip Software	PHOTOPRINT/Maintop/Riin Rip-honson						
Negative pressure	White and color separate negative pressure						
Power Supply	AC220V 50HZ ± 10%						
Temperature	20-32°C						
Humidity	40-75%						
Power	2500W						
Appearance Size (mm)	Length /width/height:2065/1180/1005						
Data Transmission	TCP/IP network interface						
Net Weight(kg)	400						
Wooden box size(mm)	2520X1550X1410						
Suction system	750W brand fans						
Y-axis	Servo motor drive						
Lead screw	Imported brand double Yscrew						